

# CATALOG



Tires | Lubricants | Batteries | Tools and supplies | Car care products  
Equipment | Brake pads | Filters | Car accessories | Wiper blades



Since 1960

81 88 81 81  
05 40 00 08  
CUSTOMER SERVICE:  
81 81 81 11  
SECTOR 32 - STREET 49  
CHOUEIFAT - LEBANON  
INFO@SAKA.COM.LB  
WWW.SAKA.COM.LB



# CROSSWIND CONTENT INDEX

## Contents

### SUMMER

---

- 03 COMFORT PEAK
- 09 SPORT PEAK
- 13 SPORT PEAK C/S

### ALL SEASON

---

- 15 CrossWind HP010 PLUS
- 18 Ultra Sport+
- 19 CROSSWIND HT<sup>2</sup>
- 21 CrossWind TrailTraxx
- 23 Rugged Traxx

### ALL WEATHER

---

- 25 GRIP PEAK 45

### WINTER

---

- 28 GRIP PEAK WINTER

# COMFORT PEAK

HIGH PERFORMANCE SUMMER



HP TIRE WITH GOOD HANDLING PERFORMANCE AND LOW NOISE



## FEATURES & BENEFITS

- ▲ Enhanced safety, shorter braking distances.
- ▲ Excellent grip and traction on wet and dry roads.
- ▲ Comfortable, reduced noise emissions.
- ▲ Excellent longevity and high mileage.
- ▲ For compact cars and medium-sized vehicles.

# COMFORT PEAK

RIM Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure		Overall Diameter		Overall Width		Tread Depth			
				kg	lbs	kPa	psi	mm	in	mm	in	mm	32nds		
13	155/80R13	79	T	4.50B	437	963	300	44	578	22.8	157	6.2	6.1	7.69	420/A/B
	175/70R13	82	T	5.00B	475	1047	300	44	576	22.7	177	7.0	6.1	7.69	420/A/B
	155/70R13	75	T	4.50B	387	853	300	44	548	21.6	157	6.2	6.9	8.69	420/A/B
	145/70R13	71	T	4.50B	345	761	300	44	534	21.0	150	5.9	6.1	7.69	420/A/B
14	205/70R14	94	T	6J	670	1477	300	44	644	25.4	209	8.2	6.6	8.31	420/A/B
	195/70R14	91	T	6J	615	1356	300	44	630	24.8	201	7.9	6.6	8.31	420/A/B
	185/70R14	88	T	5 1/2J	560	1235	300	44	616	24.3	189	7.4	6.1	7.69	420/A/B
	175/70R14	84	T	5J	500	1102	300	44	602	23.7	177	7.0	7.2	9.07	420/A/B
	165/70R14	81	T	5J	462	1019	300	44	588	23.1	170	6.7	8.2	10.33	420/A/B
	195/65R14	89	H	6J	580	1279	300	44	610	24.0	201	7.9	6.6	8.31	420/A/A
	175/65R14	82	H	5J	475	1047	300	44	584	23.0	177	7.0	8.2	10.33	420/A/A
	185/60R14	82	H	5 1/2J	475	1047	300	44	578	22.8	189	7.4	8.2	10.33	420/A/A
14	185/65R14	86	H	5 1/2J	530	1168	300	44	596	23.5	189	7.4	6.1	7.69	420/A/A
	165/65R14	79	H	5J	437	963	300	44	570	22.4	170	6.7	6.1	7.69	420/A/A
	155/65R14	75	H	4 1/2 J	387	853	300	44	558	22.0	157	6.2	6.1	7.69	420/A/A
	195/60R14	86	H	6J	530	1168	300	44	590	23.2	201	7.9	6.6	8.31	420/A/A
	175/60R14	79	H	5J	437	963	300	44	566	22.3	177	7.0	6.1	7.69	420/A/A
	165/60R14	75	H	5J	387	853	300	44	554	21.8	170	6.7	6.9	8.69	420/A/A
185/55R14	80	H	6J	450	992	300	44	560	22.0	194	7.6	6.6	8.31	420/A/A	

RIM Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure		Overall Diameter		Overall Width		Tread Depth			
				kg	lbs	kPa	psi	mm	in	mm	in	mm	32nds		
205/70R15	96	T	6J	710	1565	300	44	669	26.3	209	8.2	6.6	8.31	420/A/B	
215/65R15	100	H	6 1/2J	800	1764	340	50	661	26.0	221	8.7	6.6	8.31	420/A/A	
205/65R15	94	H	6J	670	1477	300	44	647	25.5	209	8.2	6.6	8.31	420/A/A	
195/65R15	95	H	6J	690	1521	340	50	635	25.0	201	7.9	6.6	8.31	420/A/A	
185/65R15	92	T	5 1/2J	630	1389	340	50	621	24.4	189	7.4	6.9	8.69	420/A/A	
215/60R15	94	H	6 1/2J	670	1477	300	44	639	25.2	221	8.7	6.6	8.31	420/A/A	
205/60R15	91	V	6J	615	1356	300	44	627	24.7	209	8.2	6.6	8.31	420/A/A	
165/55R15	75	V	5J	387	853	300	44	563	22.2	170	6.7	6.1	7.69	420/A/A	
175/65R15	84	H	5J	500	1102	300	44	609	24.0	177	7.0	6.1	7.69	420/A/A	
165/65R15	81	H	5J	462	1019	300	44	595	23.4	170	6.7	6.1	7.69	420/A/A	
145/65R15	72	T	4 1/2J	355	783	300	44	569	22.4	150	5.9	7	8.82	420/A/A	
15	195/60R15	88	H	6J	560	1235	300	44	615	24.2	201	7.9	7.6	9.57	420/A/A
185/60R15	88	H	5 1/2J	560	1235	340	50	603	23.7	189	7.4	7.6	9.57	420/A/A	
175/60R15	81	H	5J	462	1019	300	44	591	23.3	177	7.0	6.1	7.69	420/A/A	
165/60R15	77	H	5J	412	908	300	44	579	22.8	170	6.7	6.1	7.69	420/A/A	
155/60R15	74	T	4 1/2J	375	827	300	44	567	22.3	157	6.2	6.1	7.69	420/A/A	
205/55R15	88	V	6 1/2J	560	1235	300	44	607	23.9	214	8.4	7.1	8.94	420/A/A	
195/55R15	85	V	6J	151	1135	300	44	595	23.4	201	7.9	6.9	8.69	420/A/A	
185/55R15	82	V	6J	475	1047	300	44	585	23.0	194	7.6	7.6	9.57	420/A/A	
175/55R15	77	T	5 1/2J	412	908	300	44	573	22.6	182	7.2	7.2	9.07	420/A/A	
205/50R15	86	V	6 1/2J	530	1168	300	44	587	23.1	214	8.4	6.6	8.31	420/A/A	
195/50R15	82	V	6J	475	1047	300	44	577	22.7	201	7.9	6.9	8.69	420/A/A	
165/55R15	75	V	5J	387	853	300	44	563	22.2	170	6.7	6.1	7.69	420/A/A	

RIM Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure		Overall Diameter		Overall Width		Tread Depth			
				kg	lbs	kPa	psi	mm	in	mm	in	mm	32nds		
255/70R16	115	H	7 1/2J	1215	2679	340	50	764	30.1	260	10.2	7.9	9.95	420/A/B	
215/65R16	98	H	6 1/2J	750	1653	300	44	686	27.0	221	8.7	6.6	8.31	420/A/A	
205/65R16	95	H	6J	690	1521	300	44	672	26.5	209	8.2	6.6	8.31	420/A/A	
195/65R16	92	H	6J	630	1389	350	51	660	26.0	201	7.9	6.6	8.31	420/A/A	
235/60R16	100	H	7J	800	1764	300	44	688	27.1	240	9.4	7.4	9.32	420/A/A	
225/60R16	98	V	6 1/2J	750	1653	300	44	676	26.6	228	9.0	6.9	8.69	420/A/A	
215/60R16	99	V	6 1/2J	690	1521	300	44	664	26.1	221	8.7	6.6	8.31	420/A/A	
205/60R16	96	V	6J	710	1565	340	50	652	25.7	209	8.2	6.6	8.31	420/A/A	
195/60R16	89	H	6J	580	1279	300	44	640	25.2	201	7.9	6.6	8.31	420/A/A	
225/55R16	99	V	7J	775	1709	340	50	654	25.7	233	9.2	6.9	8.69	420/A/A	
215/55R16	93	V	7J	650	1433	300	44	642	25.3	226	8.9	6.6	8.31	420/A/A	
195/55R16	91	V	6J	615	1356	340	50	620	24.4	201	7.9	6.6	8.31	420/A/A	
16	185/55R16	83	V	6J	487	1074	300	44	610	24.0	194	7.6	7.1	8.94	420/A/A
195/50R16	88	V	6J	560	1235	340	50	602	23.7	201	7.9	6.6	8.31	420/A/A	
185/50R16	81	V	6J	462	1019	300	44	592	23.3	194	7.6	6.6	8.31	420/A/A	
205/55R16	91	V	6 1/2J	615	1356	300	44	632	24.9	214	8.4	7.6	9.57	420/A/A	
225/70R16	103	H	6 1/2J	875	1929	300	44	722	28.4	228	9.0	8.4	10.58	420/A/B	
175/60R16	82	H	5J	475	1047	300	44	616	24.3	177	7.0	6.1	7.69	420/A/A	
225/50R16	92	V	7J	630	1389	300	44	632	24.9	233	9.2	6.9	8.69	420/A/A	
205/50R16	87	V	6 1/2J	545	1201	300	44	612	24.1	214	8.4	7.6	9.57	420/A/A	
195/55R16	91	V	6J	615	1356	340	50	620	24.4	201	7.9	6.6	8.31	420/A/A	
185/55R16	83	V	6J	487	1074	300	44	610	24.0	194	7.6	7.1	8.94	420/A/A	
195/50R16	88	V	6J	560	1235	340	50	602	23.7	201	7.9	6.6	8.31	420/A/A	
185/50R16	81	V	6J	462	1019	300	44	592	23.3	194	7.6	6.6	8.31	420/A/A	

RIM Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure		Overall Diameter		Overall Width		Tread Depth		
				kg	lbs	kPa	psi	mm	in	mm	in	mm	32nds	
225/60R17	99	V	6 1/2J	775	1709	300	44	702	27.6	228	9.0	6.9	8.69	420/A/A
215/60R17	96	H	6 1/2J	710	1565	300	44	690	27.2	221	8.7	6.9	8.69	420/A/A
195/60R17	90	H	6J	600	1323	350	51	666	26.2	201	7.9	6.6	8.31	420/A/A
235/55R17	99	V	7 1/2J	775	1709	300	44	690	27.2	245	9.6	6.6	8.31	420/A/A
215/55R17	94	V	7J	670	1477	300	44	668	26.3	226	8.9	6.6	8.31	420/A/A
205/55R17	95	V	6 1/2J	690	1521	340	50	658	25.9	214	8.4	6.6	8.31	420/A/A
225/50R17	98	V	7J	750	1653	340	50	658	25.9	233	9.2	6.9	8.69	420/A/A
215/50R17	95	V	7J	690	1521	340	50	648	25.5	226	8.9	6.9	8.69	420/A/A
205/50R17	93	V	6 1/2J	650	1433	340	50	638	25.1	214	8.4	6.6	8.31	420/A/A
225/65R17	102	H	6 1/2J	850	1874	300	44	724	28.5	228	9.0	6.6	8.31	420/A/A
235/60R17	102	H	7J	850	1874	300	44	714	28.1	240	9.4	7.4	9.32	420/A/A
205/55R17	95	V	6 1/2J	690	1521	340	50	658	25.9	214	8.4	6.6	8.31	420/A/A
225/50R17	98	V	7J	750	1653	340	50	658	25.9	233	9.2	6.9	8.69	420/A/A
215/50R17	95	V	7J	690	1521	340	50	648	25.5	226	8.9	6.9	8.69	420/A/A
205/50R17	93	V	6 1/2J	650	1433	340	50	638	25.1	214	8.4	6.6	8.31	420/A/A

17



# SPORT PEAK

ULTRA HIGH PERFORMANCE SUMMER



## FEATURES & BENEFITS

- ▲ Outstanding handling, stability and control.
- ▲ Maximized grip and dry performance.
- ▲ Good levels of response for precise steering.
- ▲ Short braking distances on wet and dry roads.
- ▲ For compact cars, medium-sized vehicles, sedans and sport cars.

# SPORT PEAK

RIM Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure		Overall Diameter		Overall Width		Tread Depth		
				kg	lbs	kPa	psi	mm	in	mm	in	mm	32nds	
185/55R16	87	V	6J	545	1201	340	50	610	24.0	194	7.6	6.4	8.06	A/A
205/55R16	94	Y	6 1/2J	670	1477	340	50	632	24.9	214	8.4	7.1	8.94	A/A
215/55R16	97	Y	7J	730	1609	340	50	642	25.3	226	8.9	6.4	8.06	A/A
225/55R16	99	Y	7J	775	1709	340	50	654	25.7	233	9.2	6.4	8.06	A/A
205/50R16	91	Y	6 1/2J	615	1356	340	50	612	24.1	214	8.4	6.4	8.06	A/A
16 225/50R16	96	Y	7J	710	1565	340	50	632	24.9	233	9.2	6.4	8.06	A/A
195/45R16	84	V	6 1/2J	500	1102	340	50	582	22.9	195	7.7	6.4	8.06	A/A
205/45R16	87	Y	7J	545	1201	340	50	590	23.2	206	8.1	6.4	8.06	A/A
215/45R16	90	Y	7J	600	1323	340	50	600	23.6	213	8.4	6.4	8.06	A/A
215/40R16	86	Y	7 1/2J	530	1168	340	50	578	22.8	218	8.6	6.4	8.06	A/A
215/55R17	98	Y	7J	750	1653	340	50	668	26.3	226	8.9	6.4	8.06	A/A
225/55R17	101	Y	7J	825	1819	340	50	680	26.8	233	9.2	6.4	8.06	A/A
205/50R17	93	Y	6 1/2J	650	1433	340	50	638	25.1	214	8.4	6.4	8.06	A/A
215/50R17	95	Y	7J	690	1521	340	50	648	25.5	226	8.9	6.4	8.06	A/A
225/50R17	98	Y	7J	750	1653	340	50	658	25.9	233	9.2	7.1	8.94	A/A
17 235/50R17	100	Y	7 1/2J	800	1764	340	50	668	26.3	245	9.6	6.9	8.69	A/A
195/45R17	85	W	6 1/2J	515	1135	340	50	608	23.9	195	7.7	6.4	8.06	A/A
205/45R17	88	Y	7J	560	1235	340	50	616	24.3	206	8.1	6.4	8.06	A/A
215/45R17	91	Y	7J	615	1356	340	50	626	24.6	213	8.4	6.4	8.06	A/A

# SPORT PEAK

RIM Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure		Overall Diameter		Overall Width	Tread Depth				
				kg	lbs	kPa	psi	mm	in		mm	32nds			
17	235/45R17	97	Y	8J	730	1609	340	50	644	25.4	236	9.3	6.9	8.69	A/A
	245/45R17	99	Y	8J	775	1709	340	50	652	25.7	243	9.6	6.9	8.69	A/A
	205/40R17	84	Y	7 1/2J	500	1102	340	50	596	23.5	212	8.3	6.4	8.06	A/A
	215/40R17	87	Y	7 1/2J	545	1201	340	50	604	23.8	218	8.6	6.4	8.06	A/A
	245/40R17	95	Y	8 1/2J	690	1521	340	50	628	24.7	248	9.8	6.9	8.69	A/A
18	235/50R18	101	Y	7 1/2J	825	1819	340	50	693	27.3	245	9.6	6.9	8.69	A/A
	225/45R18	95	Y	7 1/2J	690	1521	340	50	659	25.9	225	8.9	6.4	8.06	A/A
	235/45R18	98	Y	8J	750	1653	340	50	669	26.3	236	9.3	7.1	8.94	A/A
	245/45R18	100	Y	8J	800	1764	340	50	677	26.7	243	9.6	6.9	8.69	A/A
	255/45R18	103	Y	8 1/2J	875	1929	340	50	687	27.0	255	10.0	6.9	8.69	A/A
	225/40R18	92	Y	8J	630	1389	340	50	637	25.1	230	9.1	6.4	8.06	A/A
	235/40R18	95	Y	8 1/2J	690	1521	340	50	645	25.4	241	9.5	6.9	8.69	A/A
19	245/40R18	97	Y	8 1/2J	730	1609	340	50	653	25.7	248	9.8	6.9	8.69	A/A
	255/35R18	94	Y	9J	670	1477	340	50	635	25.0	260	10.2	6.9	8.69	A/A
	265/35R18	97	Y	9 1/2J	730	1609	340	50	643	25.3	271	10.7	6.9	8.69	A/A
	225/55R19	103	Y	7J	875	1929	340	50	731	28.8	233	9.2	6.4	8.06	A/A
	235/50R19	103	Y	7 1/2J	875	1929	340	50	719	28.3	245	9.6	6.9	8.69	A/A
19	225/45R19	96	Y	7 1/2J	710	1565	340	50	685	27.0	225	8.9	6.4	8.06	A/A
	245/45R19	102	Y	8J	850	1874	340	50	703	27.7	243	9.6	6.9	8.69	A/A
	225/40R19	93	Y	8J	650	1433	340	50	663	26.1	230	9.1	6.4	8.06	A/A

# SPORT PEAK

RIM Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure		Overall Diameter		Overall Width	Tread Depth				
				kg	lbs	kPa	psi	mm	in		mm	32nds			
19	235/40R19	96	Y	8 1/2J	710	1565	340	50	671	26.4	241	9.5	6.9	8.69	A/A
	245/40R19	98	Y	8 1/2J	750	1653	340	50	679	26.7	248	9.8	6.9	8.69	A/A
	275/40R19	105	Y	9 1/2J	925	2039	340	50	703	27.7	278	10.9	6.9	8.69	A/A
	225/35R19	88	Y	8J	560	1235	340	50	641	25.2	230	9.1	7.1	8.94	A/A
	235/35R19	91	Y	8 1/2J	615	1356	340	50	647	25.5	241	9.5	6.9	8.69	A/A
20	245/35R19	93	Y	8 1/2J	650	1433	340	50	655	25.8	248	9.8	7.1	8.94	A/A
	255/35R19	96	Y	9J	710	1565	340	50	661	26.0	260	10.2	6.9	8.69	A/A
	255/30R19	91	Y	9J	615	1365	340	50	637	25.1	260	10.2	6.9	8.69	A/A
	245/40R20	99	Y	8 1/2J	775	1709	340	50	704	27.7	248	9.8	6.9	8.69	A/A
	245/35R20	95	Y	8 1/2J	690	1521	340	50	680	26.8	248	9.8	6.9	8.69	A/A
20	255/35R20	97	Y	9J	730	1609	340	50	686	27.0	260	10.2	6.9	8.69	A/A
	275/35R20	102	Y	9 1/2J	850	1874	340	50	700	27.6	278	10.9	6.9	8.69	A/A
	315/35R20	110	Y	11J	1060	2337	340	50	728	28.7	320	12.6	6.9	8.69	A/A
	215/30R20	82	W	7 1/2J	475	1047	340	50	638	25.1	218	8.6	7.1	8.94	A/A
	265/30R20	94	Y	9 1/2J	670	1477	340	50	668	26.3	271	10.7	6.9	8.69	A/A
21	245/35R21	96	Y	8 1/2J	710	1565	340	50	705	27.8	248	9.8	6.9	8.69	A/A
	295/35R21	107	Y	10 1/2J	975	2149	340	50	739	29.1	301	11.9	6.9	8.69	A/A
	255/35R22	99	Y	9J	775	1709	340	50	737	29.0	260	10.2	6.9	8.69	A/A
22	285/35R22	106	Y	10J	950	2049	340	50	759	29.9	290	11.4	6.9	8.69	A/A
	265/30R22	97	Y	9 1/2J	730	1609	340	50	719	28.3	271	10.7	6.9	8.69	A/A



## FEATURES & BENEFITS

- ▲ Enhanced safety, short braking distances.
- ▲ Precise handling, outstanding stability and control.
- ▲ Comfortable, reduces noise emissions.
- ▲ Enhanced wear performance, high mileage.
- ▲ For city SUV, SUV and modern off-road cars.

# SPORT PEAK C/S

SUV (ULTRA) HIGH PERFORMANCE SUMMER



## SPORT PEAK C/S

RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
15	205/70R15	96	H	6J	710	1565	300	44
	215/70R16	100	H	6 1/2J	800	1764	300	44
	225/65R16	100	H	6 1/2J	800	1764	300	44
16	225/75R16	104	H	6J	900	1984	300	44
	235/60R16	100	H	7J	800	1764	300	44
	235/70R16	106	H	7J	950	2094	300	44
	245/70R16 XL	111	H	7J	1090	2403	340	50
	255/70R16	111	H	7 1/2J	1090	2403	300	44

RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
16	265/70R16	112	T	8J	1120	2469	300	44
	275/70R16	114	H	8J	1180	2601	300	44
17	215/60R17	96	H	6 1/2J	710	1565	300	44
	215/65R17 XL	103	V	6 1/2J	875	1929	340	50
	225/65R17 XL	106	V	6 1/2J	950	2094	340	50
	235/60R17 XL	106	V	7J	950	2094	340	50
	235/65R17 XL	108	V	7J	1000	2205	340	50
	255/60R17	106	H	7 1/2J	950	2094	300	44
	255/65R17	110	H	7 1/2J	1060	2337	300	44
	265/65R17	112	H	8J	1120	2469	300	44
18	275/55R17	109	V	8 1/2J	1030	2271	300	44
	215/50R18	92	W	7J	630	1389	300	44
	215/55R18 XL	99	V	7J	775	1709	340	50
	225/50R18 XL	99	W	7J	775	1709	340	50
	225/55R18	98	V	7J	750	1653	300	44
	225/60R18 XL	104	V	6 1/2J	900	1984	340	50
	235/55R18 XL	104	W	7 1/2J	900	1984	340	50
	235/60R18 XL	107	W	7J	975	2149	340	50
	255/55R18 XL	109	Y	8J	1030	2271	340	50
	255/60R18 XL	112	V	7 1/2J	1120	2469	340	50
19	265/60R18	110	V	8J	1060	2337	300	44
	275/60R18	113	H	8J	1150	2535	300	44
	285/60R18	116	H	8 1/2J	1250	2756	300	44
	205/55R19 XL	97	V	6 1/2J	730	1609	340	50
	235/45R19 XL	99	V	8J	775	1709	340	50
	235/55R19 XL	105	W	7 1/2J	925	2039	340	50
	255/40R19 XL	100	W	9J	800	1764	340	50
	255/45R19 XL	104	W	8 1/2J	900	1984	340	50
	255/50R19 XL	107	W	8J	975	2149	340	50
	255/55R19 XL	111	W	8J	1090	2403	340	50
20	265/50R19 XL	110	Y	8 1/2J	1060	2337	340	50
	245/45R20 XL	103	W	8J	875	1929	340	50
	255/40R20 XL	101	W	9J	825	1819	340	50
	255/45R20 XL	105	Y	8 1/2J	925	2039	340	50
	265/45R20 XL	108	Y	9J	1000	2205	340	50
21	265/50R20 XL	111	W	8 1/2J	1090	2403	340	50
	275/45R20 XL	110	W	9J	1060	2337	340	50
	315/35R20 XL	110	Y	11J	1060	2337	340	50
	245/40R21 XL	100	W	8 1/2J	800	1764	340	50
21	255/40R21 XL	102	W	9J	850	1874	340	50
	275/45R21 XL	110	W	9J	1060	2337	340	50

# CROSSWIND HP<sup>010</sup> PLUS

PCR tire with high grip performance



## FEATURES & BENEFITS

- ▲ Adopt 3D steel sheet design to improve grip performance.
- ▲ Groove depth design with reasonable patterns increases tire wear mileage.
- ▲ The small vertical pattern design on the shoulder enhances drainage performance.

## CROSSWIND HP<sup>010</sup> PLUS

RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure		UTQG
					kg	lbs	kPa	psi	
14	175/65R14	82	H	5J	475	1047	300	44	520/A/A
	185/65R14	86	H	5 1/2J	530	1168	300	44	520/A/A
	185/70R14	88	T	5 1/2J	560	1235	300	44	440/A/B
	195/70R14	91	T	6J	615	1356	300	44	440/A/B

RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure		UTQG
					kg	lbs	kPa	psi	
15	185/60R15	84	H	5 1/2J	500	1102	300	44	520/A/A
	185/65R15	88	H	5 1/2J	560	1235	300	44	520/A/A
	195/60R15	88	H	6J	560	1235	300	44	520/A/A
	195/65R15	91	H	6J	615	1356	300	44	520/A/A
	205/60R15	91	H	6J	615	1356	300	44	520/A/A
	205/65R15	94	H	6J	670	1477	300	44	520/A/A
	215/70R15	98	T	6 1/2J	750	1653	300	44	440/A/B
16	195/55R16	87	H	6J	545	1201	300	44	520/A/A
	205/55R16	91	H	6 1/2J	615	1356	300	44	520/A/A
	205/60R16	92	H	6J	630	1389	300	44	520/A/A
	215/55R16	93	H	7J	650	1433	300	44	520/A/A
	215/60R16	95	V	6 1/2J	690	1521	300	44	520/A/A
	215/65R16	98	H	6 1/2J	750	1653	300	44	520/A/A
	215/70R16	100	T	6 1/2J	800	1764	300	44	440/A/B
	225/65R16	100	H	6 1/2J	800	1764	300	44	520/A/A
	225/60R16	98	H	6 1/2J	750	1653	300	44	520/A/A
	235/60R16	100	H	7J	800	1764	300	44	520/A/A
17	235/65R16	103	H	7J	875	1929	300	44	520/A/A
	215/45R17 XL	91	W	7J	615	1356	340	50	520/A/A
	215/50R17	91	V	7J	615	1356	300	44	520/A/A
	215/55R17	94	V	7J	670	1477	300	44	520/A/A
	215/60R17	96	H	6 1/2J	710	1565	300	44	520/A/A
	215/65R17	99	H	6 1/2J	775	1709	300	44	520/A/A
	225/45R17 XL	94	W	7 1/2J	670	1477	340	50	520/A/A
	225/50R17 XL	98	V	7J	750	1653	340	50	520/A/A
	225/55R17	97	V	7J	730	1609	300	44	520/A/A
	225/60R17	99	H	6 1/2J	775	1709	300	44	520/A/A
	225/65R17	102	H	6 1/2J	850	1874	300	44	520/A/A
	235/45R17 XL	97	V	8J	730	1609	340	50	520/A/A
	235/55R17	99	V	7 1/2J	775	1709	300	44	520/A/A
235/60R17	102	H	7J	850	1874	300	44	520/A/A	
235/65R17	104	H	7J	900	1984	300	44	520/A/A	

RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure		UTQG
					kg	lbs	kPa	psi	
18	215/55R18 XL	99	H	7J	775	1709	340	50	520/A/A
	225/40R18 XL	92	W	8J	630	1389	340	50	520/A/A
	225/45R18 XL	95	W	7 1/2J	690	1521	340	50	520/A/A
	225/50R18	95	W	7J	690	1521	300	44	520/A/A
	225/55R18	98	H	7J	750	1653	300	44	520/A/A
	225/60R18	100	H	6 1/2J	800	1764	300	44	520/A/A
	235/50R18	97	W	7 1/2J	730	1609	300	44	520/A/A
	235/55R18 XL	104	V	7 1/2J	900	1984	340	50	520/A/A
	235/60R18	103	H	7J	875	1929	300	44	520/A/A
	235/65R18	106	H	7J	950	2094	300	44	520/A/A
	245/40R18 XL	97	W	8 1/2J	730	1609	340	50	520/A/A
	245/45R18 XL	100	W	8J	800	1764	340	50	520/A/A
	245/60R18	105	H	7J	925	2039	300	44	520/A/A
	255/65R18	111	H	7 1/2J	1090	2403	300	44	520/A/A
19	225/55R19	99	V	7J	775	1709	300	44	520/A/A
	225/45R19 XL	96	W	7 1/2J	710	1565	340	50	520/A/A
	235/40R19 XL	96	V	8 1/2J	710	1565	340	50	520/A/A
	235/55R19 XL	105	V	7 1/2J	925	2039	340	50	520/A/A
	245/45R19 XL	102	V	8J	850	1874	340	50	520/A/A
	255/45R19 XL	104	V	8 1/2J	900	1984	340	50	520/A/A
	255/60R19	109	H	7 1/2J	1030	2271	300	44	520/A/A



## FEATURES & BENEFITS

- ▲ New generation of asymmetric ultra high performance tyre for summer. Make the tires have superior grip and braking performance and better handling.
- ▲ BPT Technology--improve the acture contact area for better the handling performance.
- ▲ 3D sipes improves the stiffness of block. enabling better wet performance and snow performance.

# ULTRA SPORT+

Excellent handling control  
Excellent safety on dry and wet roads



## ULTRA SPORT+

RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
20	275/40R20	106	W	9 1/2J	950	2094	340	50

# CROSSWIND HT<sup>2</sup>

All-season Performance Long&Regular Wear



## FEATURES & BENEFITS

- ▲ High performance all-season highway tire designed for North American luxury SUV.
- ▲ Excellent dry and wet handling performance maintains quiet highway driving.
- ▲ Multiple variable pitches design combined with optimized pitch ratio and arrangement reduce noise and enhance handling performance.



RIM	Size	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
					kg	lbs	kPa	psi
15	235/75R15	105	T	6 1/2J	925	2039	300	44
	215/70R16	100	H	6 1/2J	800	1764	300	44
	225/70R16	103	T	6 1/2J	875	1929	300	44
16	235/70R16	106	T	7J	950	2094	300	44
	245/70R16	107	T	7J	975	2149	300	44
	255/70R16	111	T	7 1/2J	1090	2403	300	44
	265/70R16	112	T	8J	1120	2469	300	44
	265/75R16	116	T	7 1/2J	1250	2756	300	44
	245/75R16	111	T	7J	1090	2403	300	44
17	215/65R17	99	T	6 1/2J	775	1709	300	44
	225/60R17	99	H	6 1/2J	775	1709	300	44
	235/60R17 XL	106	H	7J	950	2094	340	50
	235/65R17	104	T	7J	900	1984	300	44
	235/70R17	107	T	7J	975	2149	300	44
	245/65R17	107	T	7J	975	2149	300	44
18	245/70R17	110	T	7J	1060	2337	300	44
	255/65R17	110	T	7 1/2J	1060	2337	300	44
	265/65R17	112	T	8J	1120	2469	300	44
	225/55R18	98	H	7J	750	1653	300	44
	235/55R18 XL	104	H	7 1/2J	900	1984	340	50
	235/60R18 XL	107	H	7J	975	2149	340	50
	235/65R18	106	H	7J	950	2094	300	44
	245/60R18	105	H	7J	925	2039	300	44
19	255/55R18	105	H	8J	925	2039	300	44
	255/65R18	111	T	7 1/2J	1090	2403	300	44
	255/70R18	113	T	7 1/2J	1150	2535	300	44
	265/65R18	114	T	8J	1180	2601	300	44
	265/70R18	116	T	8J	1250	2756	300	44
20	275/65R18	116	T	8J	1250	2756	300	44
	235/55R19	101	H	7 1/2J	825	1819	300	44
	245/55R19	103	H	7 1/2J	875	1929	300	44
	255/50R19 XL	107	H	8J	975	2149	340	50
22	255/60R19	109	H	7 1/2J	1030	2271	300	44
	235/55R20	102	H	7 1/2J	850	1874	300	44
	245/60R20	107	H	7J	975	2149	300	44
	245/50R20	102	H	7 1/2J	850	1874	300	44
	255/50R20 XL	109	H	8J	1030	2271	340	50
	255/60R20 XL	113	T	8J	1150	2535	340	50
	265/50R20	107	H	8 1/2J	975	2149	300	44
275/55R20	113	H	8 1/2J	1150	2535	300	44	
20	275/60R20	115	T	8J	1215	2679	300	44
	285/45R22	110	H	9 1/2J	1060	2337	300	44

# CROSSWIND TRAILTRAXX

All weather applicability/All terrain durability



## FEATURES & BENEFITS

▲ Security assurance with any adventure, any terrain and in any weather.

▲ Driving with low noise, high traction and robustness off-road, also handling snow road easily.

▲ Outstanding mileage for heavy pickup and 4X4 vehicles.



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
16	LT225/75R16	E	115/112	Q	6J	1215/1120	2680/2470	550	80
	LT265/75R16	E	123/120	Q	7 1/2J	1550/1400	3415/3085	550	80
	LT245/75R16	E	120/116	Q	7J	1380/1260	3042/2778	550	80
	265/75R16	-	116	S	7 1/2J	1250	2756	300	44
	235/70R16	-	106	S	7J	950	2094	300	44
	LT285/75R16	E	126/123	Q	8J	1700/1550	3750/3415	550	80
	265/70R16	-	112	S	8J	1120	2469	300	44
	245/75R16	-	111	S	7J	1090	2403	300	44
17	285/70R17	-	116	T	8 1/2J	1250	2756	300	44
	LT265/70R17	E	123/120	Q	8J	1550/1400	3415/3085	550	80
	LT245/75R17	E	121/118	Q	7J	1450/1320	3195/2910	550	80
	265/70R17	-	115	S	8J	1215	2679	300	44
	LT285/70R17	E	126/123	Q	8 1/2J	1700/1550	3750/3415	550	80
	LT315/70R17	E	126/123	Q	9 1/2J	1700/1550	3750/3415	450	65
	245/65R17	-	111	H	7J	1090	2403	340	50
	35X12.50R17LT	E	125	Q	10J	1650	3640	450	65
18	265/65R17	-	116	S	8J	1250	2756	340	50
	255/70R18	-	113	T	7 1/2J	1150	2535	300	44
	LT295/70R18	E	129/126	Q	8 1/2J	1850/1700	4080/3750	550	80
	275/65R18	-	116	T	8J	1250	2756	300	44
	265/70R18	-	116	T	8J	1250	2756	300	44
	LT275/70R18	E	125/122	Q	8J	1650/1500	3640/3305	550	80
	LT275/65R18	E	123/120	Q	8J	1550/1400	3415/3085	550	80
	265/60R18	-	110	T	8J	1060	2337	300	44
20	35X12.50R18LT	F	128	Q	10J	1800	3970	550	80
	35X12.50R20LT	F	125	Q	10J	1650	3640	550	80
	275/60R20	-	115	T	8J	1215	2679	300	44
	LT275/65R20	E	126/123	Q	8J	1700/1550	3750/3415	550	80
	LT285/55R20	E	122/119	Q	9J	1500/1360	3305/3000	550	80
	275/55R20	-	117	S	8 1/2J	1285	2833	340	50
22	LT285/60R20	E	125/122	Q	8 1/2J	1650/1500	3640/3305	550	80
	33X12.50R20LT	F	119	Q	10J	1360	3000	550	80
	285/45R22	-	110	Q	9 1/2J	1060	2337	300	44
	35X12.50R22LT	F	121	Q	10J	1450	3195	550	80

# RUGGED TRAXX

High off-road traction performance/High durability



## FEATURES & BENEFITS

- ▲ High floatation: High load-carrying capacity.
- ▲ Aggressive tread pattern and sidewall design.
- ▲ The Magic Rock blocks deal with all kinds of harsh terrain and climate.
- ▲ The open shoulder grooves and large trench volume improve the drainage of mud and snow under bad road conditions.



RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
16	265/70R16	-	112	Q	8J	1120	2469	300	44
	265/75R16	-	116	Q	7 1/2J	1250	2756	300	44
	LT245/75R16	E	120/116	Q	7J	1380/1260	3042/2778	550	80
	LT285/75R16	E	126/123	Q	8J	1700/1550	3750/3415	550	80
	LT265/75R16	E	123/120	Q	7 1/2J	1550/1400	3415/3085	550	80
17	35X12.50R17LT	F	128	Q	10J	1800	3970	550	80
	265/70R17	-	115	Q	8J	1215	2679	300	44
	265/65R17	-	112	Q	8J	1120	2469	300	44
	LT245/75R17	E	121/118	Q	7J	1450/1320	3195/2910	550	80
	LT285/70R17	E	126/123	Q	8 1/2J	1700/1550	3750/3415	550	80
	LT265/70R17	E	123/120	Q	8J	1550/1400	3415/3085	550	80
18	35X12.50R18LT	F	128	Q	10J	1800	3970	550	80
	255/70R18	-	116	T	7 1/2J	1250	2756	340	50
	275/65R18	-	116	T	8J	1250	2756	340	50
	265/60R18	-	114	Q	8J	1180	2601	340	50
	265/70R18	-	116	S	8J	1250	2756	300	44
	LT275/70R18	E	125/122	Q	8J	1650/1500	3640/3305	550	80
	LT275/65R18	E	123/120	Q	8J	1550/1400	3415/3085	550	80
20	35X12.50R20LT	F	125	Q	10J	1650	3640	550	80
	275/55R20	-	117	Q	8 1/2J	1285	2833	340	50
	275/60R20	-	116	T	8J	1250	2756	340	50
	LT305/55R20	E	121/118	Q	9 1/2J	1450/1320	3195/2910	450	65
	LT275/65R20	E	126/123	Q	8J	1700/1550	3750/3415	550	80
22	LT285/60R20	E	125/122	Q	8 1/2J	1650/1500	3640/3305	550	80
	35X12.50R22LT	F	121	Q	10J	1450	3195	550	80
	37X13.50R22LT	F	128	Q	11J	1800	3970	550	80
24	285/45R22	-	114	Q	9 1/2J	1180	2601	340	50
	35X12.50R24LT	F	116	Q	10 1/2J	1250	2755	550	80

# GRIP PEAK 45

ALL SEASON



- ▲ Good traction on dry, wet and snowy roads.
- ▲ Short braking distances rain or shine.

- ▲ Excellent longevity and high mileage.
- ▲ M+S marked and 3PMSF symbol.

- ▲ For compact cars, medium-sized vehicles and SUV.

INCH	EAN	SIZE	LI	SI	XL				EPREL CODE
13	-	155/70R13	75	T	/	D	C	68 A	-
	-	155/80R13	79	T	/	D	C	68 A	-
	-	165/70R13	79	T	/	D	C	68 A	-
14	-	155/65R14	75	T	/	D	C	68 A	-
	-	165/60R14	75	H	/	D	C	68 A	-
	-	165/65R14	79	T	/	D	C	68 A	-
	-	165/70R14	81	T	/	D	C	68 A	-
	-	175/65R14	82	T	/	D	C	68 A	-
	-	175/70R14	88	T	XL	D	C	68 A	-
	-	185/60R14	82	H	/	D	B	68 A	-
15	-	185/65R14	86	H	/	D	B	68 A	-
	-	165/65R15	81	T	/	D	C	68 A	-
	-	175/65R15	88	T	XL	D	C	68 A	-
	-	185/55R15	82	H	/	D	B	68 A	-
	-	185/60R15	88	H	XL	D	B	68 A	-
	-	185/65R15	88	H	/	D	B	68 A	-
	-	195/50R15	86	H	XL	D	B	69 A	-
16	-	195/55R15	85	H	/	D	B	69 A	-
	-	195/60R15	88	H	/	D	B	69 A	-
	-	195/65R15	91	H	/	D	B	69 A	-
	-	205/65R15	94	H	/	C	B	69 A	-
	-	195/45R16	84	V	XL	D	B	69 A	-
	-	195/55R16	87	V	/	D	B	69 A	-
	-	205/55R16	91	V	/	D	B	69 A	-
	-	205/60R16	96	V	XL	C	B	69 A	-
16	-	215/55R16	97	V	XL	C	B	69 A	-
	-	215/60R16	99	V	XL	C	B	69 A	-
	-	215/65R16	102	V	XL	C	B	69 A	-

INCH	EAN	SIZE	LI	SI	XL				EPREL CODE
16	-	215/70R16	100	H	/	C	B	69 A	-
	-	245/70R16	107	H	/	C	B	72 B	-
17	-	205/45R17	88	W	XL	D	B	69 A	-
	-	205/50R17	93	V	XL	C	B	69 A	-
	-	205/55R17	95	W	XL	C	B	69 A	-
	-	215/40R17	87	V	XL	D	B	69 A	-
	-	215/45R17	91	W	XL	D	B	69 A	-
	-	215/50R17	95	W	XL	C	B	69 A	-
	-	215/55R17	98	V	XL	C	B	69 A	-
	-	215/60R17	100	V	XL	C	B	69 A	-
	-	225/45R17	94	W	XL	C	B	69 A	-
	-	225/50R17	98	V	XL	C	B	69 A	-
	-	225/55R17	101	V	XL	C	B	69 A	-
	-	225/60R17	103	V	XL	C	B	69 A	-
	-	225/65R17	106	V	XL	C	B	69 A	-
	-	235/45R17	97	W	XL	C	B	72 B	-
	-	235/55R17	103	W	XL	C	B	72 B	-
-	235/65R17	108	V	XL	C	B	72 B	-	
18	-	245/45R17	99	W	XL	C	B	72 B	-
	-	215/40R18	89	W	XL	D	B	69 A	-
	-	215/50R18	96	W	XL	C	B	69 A	-
	-	215/55R18	99	W	XL	C	B	69 A	-
	-	225/40R18	92	W	XL	C	B	69 A	-
	-	225/45R18	95	W	XL	C	B	69 A	-
	-	235/45R18	98	W	XL	C	B	72 B	-
19	-	235/55R18	100	W	/	C	B	72 B	-
	-	245/40R18	97	W	XL	C	B	72 B	-
	-	225/35R19	88	W	XL	D	B	69 A	-
	-	225/45R19	96	W	XL	C	B	69 A	-
19	-	235/35R19	91	W	XL	D	B	72 B	-
	-	245/45R19	102	W	XL	C	B	72 B	-



### FEATURES & BENEFITS

- ▲ Outstanding traction and braking performance in snow and ice.
- ▲ Enhanced performance for a safe driving experience in winter.
- ▲ High mileage.
- ▲ M+S marked and 3PMSF symbol.
- ▲ For compact cars, medium-sized vehicles and SUV.




# GRIP PEAK WINTER




(ULTRA) HIGH PERFORMANCE WINTER



## GRIP PEAK WINTER

INCH	EAN	SIZE	LI	SI	XL				EPREL CODE
14	-	165/70R14	85	T	XL	D	B	71 B	-
	-	175/65R14	82	T		D	B	71 B	-
	-	175/65R14	86	H	XL	D	B	71 B	-

INCH	EAN	SIZE	LI	SI	XL				EPREL CODE
15	-	175/65R15	88	H	XL	D	B	71 B	-
	-	185/55R15	86	V	XL	D	B	71 B	-
	-	185/60R15	88	V	XL	D	B	71 B	-
	-	185/65R15	88	T		D	B	71 B	-
	-	185/65R15	92	V	XL	D	B	71 B	-
	-	195/50R15	86	V	XL	D	B	72 B	-
	-	195/60R15	92	H	XL	D	B	72 B	-
	-	195/65R15	91	T		D	B	72 B	-
	-	195/65R15	95	V	XL	D	B	72 B	-
16	-	195/45R16	84	H	XL	D	B	72 B	-
	-	195/50R16	88	H	XL	D	B	72 B	-
	-	195/55R16	87	H		D	B	72 B	-
	-	205/45R16	87	H	XL	D	A	72 B	-
	-	205/55R16	91	H		D	A	72 B	-
	-	205/55R16	94	V	XL	D	A	72 B	-
	-	205/60R16	92	H		D	A	72 B	-
	-	205/60R16	96	V	XL	D	A	72 B	-
	-	205/65R16	95	H		D	A	72 B	-
	-	215/45R16	90	V	XL	D	A	72 B	-
	-	215/55R16	97	V	XL	D	A	72 B	-
	-	215/60R16	99	V	XL	D	A	72 B	-
	-	215/65R16	102	H	XL	D	A	72 B	-
	-	215/70R16	104	H	XL	D	A	72 B	-
	-	225/75R16	108	H	XL	C	A	72 B	-
17	-	205/45R17	88	V	XL	D	A	72 B	-
	-	205/50R17	93	V	XL	D	A	72 B	-
	-	205/55R17	95	V	XL	D	A	72 B	-
	-	205/60R17	93	H		D	A	72 B	-
	-	215/45R17	91	V	XL	D	A	72 B	-
	-	215/50R17	95	V	XL	D	A	72 B	-
	-	215/55R17	98	V		D	A	72 B	-

INCH	EAN	SIZE	LI	SI	XL				EPREL CODE	
17	-	215/60R17	100	H	XL	D	A	72 B	-	
	-	215/65R17	103	V	XL	D	A	72 B	-	
	-	225/45R17	94	W	XL	D	A	72 B	-	
	-	225/50R17	98	V	XL	D	A	72 B	-	
	-	225/55R17	101	V	XL	D	A	72 B	-	
	-	225/60R17	103	V	XL	D	A	72 B	-	
	-	225/65R17	106	V	XL	C	A	72 B	-	
	-	235/45R17	97	H	XL	D	A	72 B	-	
	-	235/55R17	103	V	XL	D	A	72 B	-	
	-	235/65R17	108	H	XL	C	A	72 B	-	
	-	245/45R17	99	V	XL	D	A	72 B	-	
	-	245/65R17	11	V	XL	C	A	72 B	-	
	-	265/65R17	11	H	XL	C	A	73 B	-	
	18	-	195/60R18	96	H	XL	D	B	72 B	-
		-	215/55R18	99	V	XL	D	A	72 B	-
-		225/40R18	92	W	XL	D	A	72 B	-	
-		225/45R18	95	W	XL	D	A	72 B	-	
-		225/50R18	99	V	XL	D	A	72 B	-	
-		225/55R18	102	V	XL	D	A	72 B	-	
-		235/45R18	98	V	XL	D	A	72 B	-	
-		235/55R18	104	V	XL	D	A	72 B	-	
-		235/60R18	107	H	XL	C	A	72 B	-	
-		245/40R18	97	V	XL	D	A	72 B	-	
-		245/45R18	100	W	XL	D	A	72 B	-	
19		-	235/55R19	105	V	XL	D	A	72 B	-
		-	245/40R19	98	V	XL	D	A	72 B	-
		-	245/45R19	102	V	XL	D	A	72 B	-
		-	255/35R19	96	V	XL	D	A	73 B	-
	-	255/40R19	100	V	XL	D	A	73 B	-	
	-	255/45R19	104	H	XL	D	A	73 B	-	

INCH	EAN	SIZE	LI	SI	XL				EPREL CODE
19	-	255/50R19	107	V	XL	C	A	73 B	-
	-	275/40R19	105	V	XL	D	A	73 B	-
20	-	245/45R20	103	H	XL	D	A	72 B	-
	-	255/35R20	97	V	XL	D	A	73 B	-
	-	275/40R20	106	V	XL	C	A	73 B	-
	-	315/35R20	110	V	XL	C	A	75 B	-



# Contents

## 1 LONG HAUL

CW-LT01	03
CWS10E	04
CWD10E	05
CWT10E	06

## 2 REGIONAL

CW-RS03	09
CW-RD03	10
CW-RT03	11
CW-HS02	12
CW-HD02	13
CWD20E	14
CWD30K	15
CWS20E	16
CWS30K	17
CWT30K	18

## 03-06

## 09-19

## 3 ON&OFF ROAD

CW-MA04	21
CW-MD04	22
CWA40K	23
CWA40X	24
CWD40K	25

## 4 LIGHT TRUCK

CW-HS02	27
CW-HD02	28
CW-HT02	29
CWT20E	30
CWS20E	31
CWD20E	32

## 5 WINTER

CW-WD06	35
CW-WS06	36

## 6 COACH&URBAN

CWA80U	38
--------	----

## 21-25

## 27-32

## 35-36

## 38-38

# LONG HAUL



**CW-LT01**

P03

**CWS10E**

P04

**CWD10E**

P05

**CWT10E**

P06

LONG HAUL

REGIONAL

ON&OFF ROAD

LIGHT TRUCK

WINTER

COACH&URBAN



# CW-LT01

SERBIA

Radial Truck Tire  
(For international long-distance transportation)

- 1 Center ribs stiffeners with hidden grooves for wear and cornering performance.
- 2 Edge blades to prevent groove edge river wear.
- 3 Blades variable depth for optimum rib flexion, uniform wear and wet braking performance.



TRAILER

Suitable for trailer axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
385/55R19.5	18	156	J	12.25	--	--	4000	900	919	386	11.5	ETRTO
435/50R19.5	20	160	J	14.00	--	--	4500	900	931	438	11.5	ETRTO
445/45R19.5	20	160	J	15.00	--	--	4500	900	895	446	10.5	ETRTO

# CWS10E

SERBIA

Radial Truck Tire  
(For international long-distance transportation)

- 1 Low rolling resistance, reducing fuel consumption.
- 2 Lasting grip and stability by hidden groove design.
- 3 New pattern design improves mileage for long-distance transportation.



STEER

Suitable for steer axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
315/80R22.5	18	154/150	M	9.00	3350	825	3750	825	1076	312	15.0	ETRTO
315/80R22.5	20	156/150(154/150)	L(M)	9.00	3350	850	4000	850	1076	312	15.0	ETRTO
315/80R22.5	22	158/150(154/150)	L(M)	9.00	3350	900	4250	900	1076	312	15.0	ETRTO
295/80R22.5	18	154/149	M	9.00	3250	850	3750	850	1044	298	14.0	ETRTO
295/80R22.5	16	152/148	M	9.00	3150	850	3550	850	1044	298	14.0	ETRTO
315/70R22.5	16	154/150(152/148)	L(M)	9.00	3350	900	3750	900	1014	312	15.0	ETRTO
315/70R22.5	18	156/150(154/150)	L(M)	9.00	3350	900	4000	900	1014	312	15.0	ETRTO
315/60R22.5	16	152/148	L	9.75	3150	900	3550	900	950	313	12.5	ETRTO
315/60R22.5	18	154/150(152/148)	L(M)	9.75	3350	900	3750	900	950	313	12.5	ETRTO
295/60R22.5	16	150/147	L	9.00	3075	900	3350	900	926	292	13.0	ETRTO



# CWD10E

SERBIA

Radial Truck Tire  
(For international long-distance transportation)

- 1** Low rolling resistance reduces fuel consumption.
- 2** Lasting grip and stability by hidden groove design with M+S and 3PMSF marking.
- 3** New pattern design improves mileage for long distance transportation.



DRIVE

Suitable for drive axle of trucks running with high speed on highway.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
315/80R22.5	18	154/150	M	9.00	3350	825	3750	825	1076	312	17.0	ETRTO
315/80R22.5	20	156/150(154/150)	L(M)	9.00	3350	850	4000	850	1076	312	17.0	ETRTO
295/80R22.5	16	152/148	M	9.00	3150	850	3550	850	1044	298	16.0	ETRTO
295/80R22.5	18	154/149	M	9.00	3250	850	3750	850	1044	298	16.0	ETRTO
315/70R22.5	16	154/150(152/148)	L(M)	9.00	3350	900	3750	900	1014	312	16.5	ETRTO
315/70R22.5	18	156/150(154/150)	L(M)	9.00	3350	900	4000	900	1014	312	16.5	ETRTO
315/60R22.5	16	152/148	L	9.75	3150	900	3550	900	950	313	14.5	ETRTO
295/60R22.5	16	150/147	L	9.00	3075	900	3350	900	926	292	16.0	ETRTO

# CWT10E

SERBIA

Radial Truck Tire  
(For international long-distance transportation)

- 1** Low rolling resistance reduces fuel consumption.
- 2** Lasting grip and stability by hidden groove design.
- 3** New pattern design improves mileage for long-distance transportation.



TRAILER

Suitable for trailer axle of trucks running with high speed on highway.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
385/55R19.5	18	156	J	12.25	--	--	4000	900	919	386	12.5	ETRTO
385/55R22.5	18	158	L	12.25	--	--	4250	850	996	386	12.0	ETRTO
385/55R22.5	20	160(158)	K(L)	12.25	--	--	4500	900	996	386	12.0	ETRTO
385/65R22.5	20	160(158)	K(L)	11.75	--	--	4500	900	1072	389	13.5	ETRTO
385/65R22.5	24	164(158)	K(L)	11.75	--	--	5000	900	1072	389	13.5	ETRTO
425/65R22.5	18	162	K	12.25	--	--	4750	760	1124	422	14.5	TRA
425/65R22.5	20	165	K	12.25	--	--	5150	825	1124	422	14.5	ETRTO
435/50R19.5	18	156	J	14.00	--	--	4000	850	931	438	12.5	ETRTO
435/50R19.5	20	160	J	14.00	--	--	4500	900	931	438	12.5	ETRTO
445/45R19.5	18	156	J	15.00	--	--	4000	900	895	446	12.5	ETRTO
445/45R19.5	20	160	J	15.00	--	--	4500	900	895	446	12.5	ETRTO



# REGIONAL



**CW-RS03** **CW-RD03** **CW-RT03** **CW-HS02** **CW-HD02**

P09 P10 P11 P12 P13



**CWD20E** **CWD30K** **CWS20E** **CWS30K** **CWT30K**

P14 P15 P16 P17 P18

LONG HAUL

REGIONAL

ON&OFF ROAD

LIGHT TRUCK

WINTER

COACH&URBAN



# CW-RS03 SERBIA

- 1 Blades variable depth for optimum rib flexion, uniform wear and wet braking performance.
- 2 Slightly directional design to provide grip in forward & braking direction.
- 3 Groove stone ejectors help prevent stone trapping and drilling to enhance casing toughness and retreadability.



STEER

Suitable for steer axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
295/60R22.5	16	150/147	L	9.00	3075	900	3350	900	926	292	12.5	ETRTO
315/60R22.5	16	152/148	L	9.75	3150	900	3550	900	950	313	13.0	ETRTO
295/80R22.5	18	154/149	M	9.00	3250	850	3750	850	1044	298	14.5	ETRTO
315/70R22.5	18	156/150(154/150)	L(M)	9.00	3350	900	4000	900	1014	312	14.5	ETRTO
315/80R22.5	22	158/150(154/150)	L(M)	9.00	3350	900	4250	900	1076	312	14.5	ETRTO
385/55R22.5	20	160(158)	K(L)	12.25	--	--	4500	900	996	386	12.5	ETRTO
385/65R22.5	24	164(158)	K(L)	11.75	--	--	5000	900	1072	389	14.5	ETRTO

# CW-RD03 SERBIA

- 1 New sipes Improve grip and resistance to tread tearing in severe conditions of use.
- 2 New groove shapes provides greater traction on slippery road surfaces.



DRIVE

Suitable for drive axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
295/60R22.5	16	150/147	L	9.00	3075	900	3350	900	926	292	16.0	ETRTO
295/80R22.5	18	154/149	L	9.00	3250	850	3750	850	1044	298	18.5	ETRTO
315/60R22.5	16	152/148	L	9.75	3150	900	3550	900	950	313	17.5	ETRTO
315/70R22.5	18	156/150(154/150)	L(M)	9.00	3350	900	4000	900	1014	312	20.0	ETRTO
315/80R22.5	20	156/150(154/150)	L(M)	9.00	3350	850	4000	850	1076	312	20.0	ETRTO

LONG HAUL

REGIONAL

ON&OFF ROAD

LIGHT TRUCK

WINTER

COACH&URBAN



# CW-RT03

SERBIA

- 1 New sipes Improve grip and resistance to tread tearing in severe conditions of use.
- 2 New groove shapes provides greater traction on slippery road surfaces.



TRAILER

Suitable for trailer axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
385/55R22.5	20	160(158)	K(L)	12.25	--	---	4500	900	996	386	12.5	ETRTO
385/65R22.5	20	164(158)	K(L)	11.75	--	---	5000	900	1072	389	13.5	ETRTO
425/65R22.5	20	165	K	12.25	--	---	5150	825	1124	422	14.0	ETRTO

# CW-HS02

SERBIA

- 1 Suitable for medium trucks running on the high-grade road.
- 2 Stone rejection design protect groove bottom from stone puncture.
- 3 Safe driving and braking thanks to 4 Z-shaped longitudinal grooves.



STEER

Suitable for steer axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
265/70R17.5	16	140/138	M	7.50	2360	800	2500	800	817	262	12.0	ETRTO
265/70R17.5	18	145/143	J	7.50	2725	900	2900	900	817	262	12.0	ETRTO
265/70R19.5	14	136/134	M	7.50	2120	725	2240	725	867	262	12.0	ETRTO
265/70R19.5	16	140/138	M	7.50	2360	775	2500	775	867	262	12.0	ETRTO
265/70R19.5	18	143/141	J	7.50	2575	850	2725	850	867	262	12.0	ETRTO
305/70R19.5	18	148/145	M	9.00(8.25)	3150	850	2900	850	923	305	12.0	ETRTO

LONG HAUL

REGIONAL

ON&OFF ROAD

LIGHT TRUCK

WINTER

COACH&URBAN



# CW-HD02 SERBIA

- 1 Suitable for medium trucks running on the high-grade road.
- 2 New siping design improves wet performance.
- 3 Low rolling resistance, reducing fuel consumption.



Suitable for drive axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
265/70R17.5	16	140/138	M	7.50	2360	800	2500	800	817	262	14.0	ETRTO
265/70R19.5	14	136/134	M	7.50	2120	725	2240	725	867	262	14.0	ETRTO
265/70R19.5	16	140/138	M	7.50	2360	775	2500	775	867	262	14.0	ETRTO
305/70R19.5	18	148/145	M	9.00(8.25)	3150	850	2900	850	923	305	13.5	ETRTO

# CWD20E SERBIA

## Radial Truck Tire

- 1 Typical block pattern design suitable for the drive axle of trucks.
- 2 Good braking and grip on the road.



Suitable for drive axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
265/70R19.5	14	136/134	M	7.50	2120	725	2240	725	867	262	15.5	ETRTO
265/70R19.5	16	140/138	M	7.50	2360	775	2500	775	867	262	15.5	ETRTO
285/70R19.5	18	146/144	M	8.25	2800	900	3000	900	895	283	16.0	ETRTO
305/70R19.5	16	144/141	M	9.00	2575	760	2800	760	923	305	13.5	TRA
305/70R19.5	18	146/143	M	9.00	2725	830	3000	830	923	305	13.5	TRA
305/70R19.5	18	148/145	M	9.00(8.25)	2900	850	3150	850	923	305	13.5	ETRTO

LONG HAUL

REGIONAL

ON&OFF ROAD

LIGHT TRUCK

WINTER

COACH&URBAN



# CWD30K

SERBIA

Radial Truck Tire  
(For national and regional transportation)

- 1 Optimization of the shoulder block improves resistance to shoulder damage.
- 2 Lasting grip and stability with M+S and 3PMSF marking.
- 3 High wear resistance.



DRIVE

Suitable for the drive axle of trucks running under a wide range of use, from highway to light unpaved road.



# CWS20E

SERBIA

Radial Truck Tire (Regional Steer)

- 1 Long life.
- 2 Retreadability.
- 3 Low eccentric wear.



STEER

Suitable for steer axle of trucks running with high speed on highway.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
				kg	kpa	kg	kpa					
11R22.5	16	146/143	L	8.25	2725	830	3000	830	1065	279	22.0	TRA
11R22.5	14	144/142	L	8.25	2650	720	2800	720	1065	279	22.0	TRA
12R22.5	16	152/148	L	9.00	3150	850	3550	850	1084	300	22.0	ETRTO
12R22.5	18	152/149	L	9.00	3250	930	3550	930	1085	300	22.0	GB
295/80R22.5	16	152/148	M	9.00	3150	850	3550	850	1044	298	20.5	ETRTO
295/80R22.5	18	152/149	M	9.00	3250	900	3550	900	1044	298	20.5	GB
315/80R22.5	18	154/150	M	9.00	3350	825	3750	825	1076	312	22.0	ETRTO
315/80R22.5	20	156/150(154/150)	L(M)	9.00	3350	850	4000	850	1076	312	22.0	ETRTO
315/70R22.5	16	154/150(152/148)	L(M)	9.00	3350	900	3750	900	1014	312	20.0	ETRTO
315/70R22.5	18	156/150(154/150)	L(M)	9.00	3350	900	4000	900	1014	312	20.0	ETRTO
315/60R22.5	16	152/148	L	9.75	3150	900	3550	900	950	313	17.5	ETRTO
295/60R22.5	16	150/147	L	9.00	3075	900	3350	900	926	292	18.0	ETRTO

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
				kg	kpa	kg	kpa					
265/70R19.5	14	136/134	M	7.50	2120	725	2240	725	867	262	13.5	ETRTO
265/70R19.5	16	140/138	M	7.50	2360	775	2500	775	867	262	13.5	ETRTO
265/70R19.5	18	143/141	J	7.50	2575	850	2725	850	867	262	13.5	ETRTO
285/70R19.5	18	146/144	M	8.25	2800	900	3000	900	895	283	13.5	ETRTO
285/70R19.5	20	150/148	J	8.25	3150	900	3350	900	895	283	13.5	ETRTO
305/70R19.5	16	144/141	M	9.00	2575	760	2800	760	923	305	12.0	TRA
305/70R19.5	18	146/143	M	9.00	2725	830	3000	830	923	305	12.0	TRA
305/70R19.5	18	148/145	M	9.00(8.25)	2900	850	3150	850	923	305	12.0	ETRTO



# CWS30K

Radial Truck Tire  
(For national and regional transportation)

- 1 Optimization of the shoulder block improves resistance to shoulder damage.
- 2 Lasting grip and stability with stone rejection design.
- 3 High wear resistance.



STEER

Suitable for the steer axle of trucks running under a wide range of use, from highway to light unpaved road.



# CWT30K

SERBIA

Radial Truck Tire (Regional Trailer)

- 1 Typical combined pattern design offers optimal trailer performance.
- 2 Low rolling resistance.
- 3 Wear-resistance compound reduces shifting to prevent uneven wear.



TRAILER

Suitable for trailer axle of trucks running with high speed on highway.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
11R22.5	16	146/143	L	8.25	2725	830	3000	830	1054	279	165	TRA
11R22.5	14	144/142	L	8.25	2650	720	2800	720	1054	279	165	TRA
12R22.5	16	152/148	L	9.00	3150	850	3550	850	1084	300	170	ETRTO
295/80R22.5	18	154/149	M	9.00	3250	850	3750	850	1044	298	165	ETRTO
295/80R22.5	16	152/148	M	9.00	3150	850	3550	850	1044	298	165	ETRTO
315/80R22.5	18	154/150	M	9.00	3350	825	3750	825	1076	312	155	ETRTO
315/80R22.5	20	156/150(154/150)	L(M)	9.00	3350	850	4000	850	1076	312	155	ETRTO
315/80R22.5	20	157/154	L	9.00	3750	900	4125	900	1076	312	155	TRA
315/80R22.5	22	158/150(154/150)	L(M)	9.00	3350	900	4250	900	1076	312	155	ETRTO
315/70R22.5	16	154/150(152/148)	L(M)	9.00	3350	900	3750	900	1014	312	155	ETRTO
315/70R22.5	18	156/150(154/150)	L(M)	9.00	3350	900	4000	900	1014	312	155	ETRTO
315/60R22.5	16	152/148	L	9.75	3150	900	3550	900	950	313	125	ETRTO
315/60R22.5	18	154/150(152/148)	L(M)	9.75	3350	900	3750	900	950	313	125	ETRTO
295/60R22.5	16	150/147	L	9.00	3075	900	3350	900	926	292	140	ETRTO
385/55R22.5	18	158	L	12.25	--	--	4250	850	996	386	135	ETRTO
385/55R22.5	20	160(158)	K(L)	12.25	--	--	4500	900	996	386	135	ETRTO
385/65R22.5	20	160(158)	K(L)	11.75	--	--	4500	900	1072	389	155	ETRTO
385/65R22.5	24	164(158)	K(L)	11.75	--	--	5000	900	1072	389	155	ETRTO

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
385/65R22.5	18	158	L	11.75	---	---	4250	850	1072	389	165	ETRTO
385/65R22.5	20	160(158)	J(L)	11.75	---	---	4500	900	1072	389	165	ETRTO
385/65R22.5	24	164	J	11.75	---	---	5000	900	1072	389	165	ETRTO
385/65R22.5	24	164(158)	K(L)	11.75	---	---	5000	900	1072	389	165	ETRTO
425/65R22.5	18	162	K	12.25	---	---	4750	760	1124	422	175	TRA
425/65R22.5	20	165	K	12.25	---	---	5150	825	1124	422	175	ETRTO
445/65R22.5	20	169	J	13.00	---	---	5800	900	1150	444	180	ETRTO
385/55R22.5	18	158	L	12.25	---	---	4250	850	996	386	165	ETRTO
385/55R22.5	20	160(158)	J(L)	12.25	---	---	4500	900	996	386	165	ETRTO



# ON&OFF ROAD



**CW-MA04**

P21

**CW-MD04**

P22

**CWA40K**

P23

**CWA40X**

P24

**CWD40K**

P25

LONG HAUL

REGIONAL

ON&OFF ROAD

LIGHT TRUCK

WINTER

COACH&URBAN



# CW-MA04 SERBIA

- 1** Tread Compound helps resist cuts and chips for enhanced retreadability.
- 2** Groove stone ejectors help prevent stone trapping and drilling to enhance casing toughness and retreadability.
- 3** All-position tread design helps enhance traction on and off the road.



All Position

Suitable for all position axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
13R22.5	20	158/156	K	9.75	4000	900	4250	900	1124	320	17.0	ETRTO
315/80R22.5	22	158/150	K	9.00	3350	900	4250	900	1076	312	17.0	ETRTO

# CW-MD04 SERBIA

- 1** Progressive, variable-width grooves, less stone retention.
- 2** New groove shapes provides greater traction on slippery road surfaces.
- 3** New tread compound improved resistance to wear and tear.



DRIVE

Suitable for drive axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
13R22.5	20	158/156	K	9.75	4000	900	4250	900	1124	320	19.0	ETRTO
315/80R22.5	22	158/150	K	9.00	3350	900	4250	900	1076	312	19.0	ETRTO

LONG HAUL

REGIONAL

ON&OFF ROAD

LIGHT TRUCK

WINTER

COACH&URBAN



# CWA40K

SERBIA

Radial Truck Tire (On&Off Road)

- 1 Thick sidewall design protects against sidewall impacts and bruises.
- 2 Stone rejection design protects groove bottom from stone puncture.
- 3 Lasting grip and stability with M+S and 3PMSF marking.



ALL POSITION

Suitable for all position axle of trucks running with high speed on highway.



# CWA40X

SERBIA

Radial Truck Tire (On&Off Road)

- 1 Thick sidewall design protects against sidewall impacts and bruises.
- 2 Stone rejection design protects groove bottom from stone puncture.
- 3 Lasting grip and stability with M+S marking.



TRAILER/STEER

Suitable for trailer/steer axle of trucks running with high speed on highway.



Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
8.25R20	14	136/134	K	6.5	2120	830	2240	830	974	236	155	GB
8.25R20	16	139/137	K	6.5	2300	930	2430	930	974	236	155	GB
9.00R20	16	144/142	K	7.0	2650	900	2800	900	1019	259	160	GB
10.00R20	18	149/146	K	7.5	3000	930	3250	930	1054	278	160	GB
11.00R20	18	152/149	K	8.0	3250	930	3550	930	1085	293	165	GB
11.00R20	16	150/147	K	8.0	3075	830	3350	830	1085	293	165	GB
12.00R20	18	154/151	K	8.5	3450	830	3750	830	1125	315	170	GB
12.00R20	20	156/153	K	8.5	3650	900	4000	900	1125	315	170	GB
12R22.5	16	152/148	F	9.00	3150	850	3550	850	1084	300	170	ETRTO
12R22.5	18	152/149	K	9.00	3250	930	3550	930	1085	300	170	GB
295/80R22.5	18	152/149	K	9.00	3250	900	3550	900	1044	298	190	GB
13R22.5	18	156/150	K	9.75	3350	875	4000	875	1124	320	190	ETRTO
13R22.5	20	158/156	K	9.75	4000	900	4250	900	1124	320	190	ETRTO
295/80R22.5	16	152/148	K	9.00	3150	850	3550	850	1044	298	190	ETRTO
315/80R22.5	18	154/150	K	9.00	3350	825	3750	825	1076	312	190	ETRTO
315/80R22.5	20	156/150	K	9.00	3350	850	4000	850	1076	312	190	ETRTO
315/80R22.5	22	158/150	K	9.00	3350	900	4250	900	1076	312	190	ETRTO
425/65R22.5	20	165	K	13.0	---	---	5150	825	1124	430	185	ETRTO
445/65R22.5	20	169	J/K	14.0	---	---	5800	900	1150	454	185	ETRTO

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
385/65R22.5	18	158	L	11.75	---	---	4250	850	1072	389	18.0	ETRTO
385/65R22.5	20	160(158)	K(L)	11.75	---	---	4500	900	1072	389	18.0	ETRTO
385/65R22.5	24	164	J	11.75	---	---	5000	900	1072	389	18.0	ETRTO
425/65R22.5	20	165	K	12.25	---	---	5150	825	1124	422	18.5	ETRTO



# CWD40K

SERBIA

## Radial Truck Tire (On&Off Road)

- 1** Thick sidewall design protects against sidewall impacts and bruises.
- 2** Stone rejection design protects groove bottom from stone puncture.
- 3** Lasting grip and stability with M+S and 3PMSF marking.



DRIVE

Suitable for drive axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual	Single						
					kg	kpa	kg	kpa				
13R22.5	18	156/150	K	9.75	3350	875	4000	875	1124	320	21.0	ETRTO
315/80R22.5	18	154/150	K	9.00	3350	825	3750	825	1076	312	21.0	ETRTO
315/80R22.5	20	156/150	K	9.00	3350	850	4000	850	1076	312	21.0	ETRTO



**CW-HS02 CW-HD02 CW-HT02 CWT20E CWS20E CWD20E**

P27

P28

P29

P30

P31

P32

LONG HAUL

REGIONAL

ON&OFF ROAD

LIGHT TRUCK

WINTER

COACH&URBAN



# CW-HS02

SERBIA

- 1 Suitable for medium trucks running on the high-grade road.
- 2 Stone rejection design protect groove bottom from stone puncture.
- 3 Safe driving and braking thanks to 4 Z-shaped longitudinal grooves.



STEER

Suitable for the steer axle of trucks running under a wide range of use, from highway to light unpaved road.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
205/75R17.5	14	124/122	M	6.00	1500	750	1600	750	753	204	10.5	ETRTO
215/75R17.5	14	126/124	M	6.00	1600	700	1700	700	767	211	10.5	ETRTO
215/75R17.5	16	135/133	J	6.00	2060	850	2180	850	767	211	10.5	ETRTO
225/75R17.5	12	126/125	M	6.75	1650	675	1700	675	783	226	11.0	ETRTO
225/75R17.5	14	129/127	M	6.75	1750	725	1850	725	783	226	11.0	ETRTO
235/75R17.5	14	132/130	M	6.75	1900	775	2000	775	797	233	11.0	ETRTO
235/75R17.5	16	141/140	J	6.75	2500	850	2575	850	797	233	11.0	ETRTO
235/75R17.5	18	143/141	J	6.75	2575	875	2725	875	797	233	11.0	ETRTO
245/70R17.5	14	134/132	M	7.50	2000	775	2120	775	789	248	11.0	ETRTO
245/70R17.5	16	136/134	M	7.50	2120	850	2240	850	789	248	11.0	ETRTO
245/70R17.5	18	143/141	J	7.50	2575	900	2725	900	789	248	11.0	ETRTO
245/70R19.5	14	133/131	M	7.50	1950	750	2060	750	839	248	11.0	ETRTO
245/70R19.5	16	136/134	M	7.50	2120	825	2240	825	839	248	11.0	ETRTO
245/70R19.5	18	141/140	J	7.50	2500	850	2575	850	839	248	11.0	ETRTO

# CW-HD02

SERBIA

- 1 Suitable for medium trucks running on the high-grade road.
- 2 New siping design improves wet performance.
- 3 Low rolling resistance, reducing fuel consumption.



DRIVE

Suitable for drive axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
205/75R17.5	14	124/122	M	6.00	1500	750	1600	750	753	204	11.5	ETRTO
215/75R17.5	14	126/124	M	6.00	1600	700	1700	700	767	211	11.5	ETRTO
225/75R17.5	12	126/125	M	6.75	1650	675	1700	675	783	226	12.0	ETRTO
225/75R17.5	14	129/127	M	6.75	1750	725	1850	725	783	226	12.0	ETRTO
235/75R17.5	14	132/130	M	6.75	1900	775	2000	775	797	233	12.0	ETRTO
235/75R17.5	16	141/140	J	6.75	2500	850	2575	850	797	233	12.0	ETRTO
245/70R17.5	14	134/132	M	7.50	2000	775	2120	775	789	248	13.0	ETRTO
245/70R17.5	16	136/134	M	7.50	2120	850	2240	850	789	248	13.0	ETRTO
245/70R19.5	14	133/131	M	7.50	1950	750	2060	750	839	248	13.0	ETRTO
245/70R19.5	16	136/134	M	7.50	2120	825	2240	825	839	248	13.0	ETRTO



# CW-HT02

SERBIA

- 1 Suitable for medium trucks running on the high-grade road.
- 2 New siping design improves wet performance.
- 3 Low rolling resistance, reducing fuel consumption.



TRAILER

Suitable for trailer axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
205/65R17.5	16	129/127 (132/132)	J(G)	6.00	1750	900	1850	900	711	204	12.5	ETRTO
215/75R17.5	16	135/133	J	6.00	2060	850	2180	850	767	211	11.0	ETRTO
235/75R17.5	16	141/140	J	6.75	2500	850	2575	850	797	233	11.0	ETRTO
235/75R17.5	18	143/141	J	6.75	2575	875	2725	875	797	233	11.0	ETRTO
235/75R17.5	18	143/141 (145/145)	J(F)	6.75	2575	875	2725	875	797	233	11.0	ETRTO
245/70R17.5	18	143/141	J	7.50	2575	900	2725	900	789	248	11.0	ETRTO
245/70R17.5	18	143/141 (146/146)	J(F)	7.50	2575	900	2725	900	789	248	11.0	ETRTO



# CWT20E

SERBIA

Radial Truck Tire (Regional Trailer)

- 1 Suitable for medium trucks running on the high-grade road.



TRAILER

Suitable for trailer axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
205/65R17.5	16	129/127 (132/132)	J(G)	6.00	1750	900	1850	900	711	205	12.5	ETRTO
215/75R17.5	14	125/122	L	6.00	1500	760	1650	760	767	211	12.5	GB
215/75R17.5	14	126/124	M	6.00	1600	700	1700	700	767	211	12.5	ETRTO
215/75R17.5	16	127/124	J	6.00	1600	830	1750	830	767	211	12.5	GB
215/75R17.5	16	135/133	J	6.00	2060	850	2180	850	767	211	12.5	ETRTO
235/75R17.5	14	132/130	M	6.75	1900	775	2000	775	797	233	12.5	ETRTO
235/75R17.5	16	141/140	J	6.75	2500	850	2575	850	797	233	12.5	ETRTO
235/75R17.5	18	143/141	J	6.75	2575	875	2725	875	797	233	12.5	ETRTO
245/70R17.5	14	134/132	M	7.50	2000	775	2120	775	789	248	12.5	ETRTO
245/70R17.5	16	136/134	M	7.50	2120	850	2240	850	789	248	12.5	ETRTO
245/70R17.5	18	143/141	J	7.50	2575	875	2725	875	789	248	12.5	ETRTO



# CWS20E

SERBIA

- 1 Suitable for medium trucks running on the high-grade road.
- 2 Stone rejection design protect groove bottom from stone puncture.
- 3 Safe driving and braking thanks to 4 Z-shaped longitudinal grooves.



STEER

Suitable for steer axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
205/75R17.5	14	124/122	M	6.00	1500	750	1600	750	753	204	10.5	ETRTO
215/75R17.5	14	126/124	M	6.00	1600	700	1700	700	767	211	11.5	ETRTO
225/75R17.5	14	129/127	M	6.75	1750	725	1850	725	783	226	11.5	ETRTO
235/75R17.5	14	132/130	M	6.75	1900	775	2000	775	797	233	12.5	ETRTO
245/70R17.5	16	136/134	M	7.50	2120	850	2240	850	789	248	12.5	ETRTO
245/70R19.5	16	136/134	M	7.50	2120	825	2240	825	839	248	12.5	ETRTO
245/70R19.5	18	141/140	J	7.50	2500	850	2575	850	839	248	12.5	ETRTO
265/70R17.5	16	140/138	M	7.50	2360	800	2500	800	817	262	13.5	ETRTO
265/70R17.5	18	145/143	J	7.50	2725	900	2900	900	817	262	13.5	ETRTO

# CWD20E

SERBIA

- 1 Typical block pattern design suitable for the drive axle of trucks.
- 2 Good braking and grip on the road.



DRIVE

Suitable for trailer axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
205/75R17.5	14	124/122	M	6.00	1500	750	1600	750	753	204	11.5	ETRTO
215/75R17.5	14	126/124	M	6.00	1600	700	1700	700	767	211	12.5	ETRTO
225/75R17.5	14	129/127	M	6.75	1750	725	1850	725	783	226	12.5	ETRTO
235/75R17.5	14	132/130	M	6.75	1900	775	2000	775	797	233	13.5	ETRTO
245/70R17.5	16	136/134	M	7.50	2120	850	2240	850	789	248	14.5	ETRTO
245/70R19.5	16	136/134	M	7.50	2120	825	2240	825	839	248	14.5	ETRTO
265/70R17.5	16	140/138	M	7.50	2360	800	2500	800	817	262	15.5	ETRTO



# WINTER



**CW-WD06**

P35



**CW-WS06**

P36

LONG HAUL

REGIONAL

ON&OFF ROAD

LIGHT TRUCK

WINTER

COACH&URBAN



# CW-WS06

SERBIA

- 1** Suitable for steer and trailer axle of trucks under snow condition.
- 2** Deeper and higher density of lateral grooves and sipes for better grip.
- 3** Zig-Zag grooves design provides excellent traction on icy and wet road condition.



STEER

Suitable for steer axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
295/80R22.5	18	154/149	M	9.00	3250	850	3750	850	1044	298	15.5	ETRTO
315/70R22.5	16	154/150(152/148)	L(M)	9.00	3350	900	3750	900	1014	312	15.5	ETRTO
315/70R22.5	18	156/150(154/150)	L(M)	9.00	3350	900	4000	900	1014	312	15.5	ETRTO
315/80R22.5	22	158/150(154/150)	L(M)	9.00	3350	900	4250	900	1076	312	15.5	ETRTO
385/55R22.5	20	160(158)	K(L)	12.25	--	--	4500	900	996	386	13.5	ETRTO
385/65R22.5	24	164(158)	K(L)	11.75	--	--	5000	900	1072	389	15.5	ETRTO

# CW-WD06

SERBIA

- 1** Suitable for drive axle of trucks under snow condition.
- 2** Lasting grip and stability, with 3PMSF marking.
- 3** Optimized rib contact combats uneven wear and improves wet handling and braking.



DRIVE

Suitable for drive axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual		Single					
					kg	kpa	kg	kpa				
295/80R22.5	18	154/149	M	9.00	3250	850	3750	850	1044	298	18.5	ETRTO
315/70R22.5	18	156/150(154/150)	L(M)	9.00	3350	900	4000	900	1014	312	20.0	ETRTO
315/80R22.5	22	158/150(154/150)	L(M)	9.00	3350	900	4250	900	1076	312	20.0	ETRTO

LONG HAUL

REGIONAL

ON&OFF ROAD

LIGHT TRUCK

WINTER

COACH&URBAN



# CWA80U

SERBIA

Radial Bus Tire (Urban all position)

- 1 Enhanced sidewall ensures high safety.
- 2 Tire strength is increased by 35%, with application of ST steel cord.
- 3 Tire bead cracking is prevented, with application of fiber layer in bead area.



Suitable for all position axle of trucks running with high speed on highway.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max Load and Inflated Pressure				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Operation Norm
					Dual kg	kpa	Single kg	kpa				
275/70R22.5	16	148/145	J	8.25	2900	900	3150	900	958	276	19.0	ETRTO



LONG HAUL

REGIONAL

ON&OFF ROAD

LIGHT TRUCK

WINTER

COACH&URBAN